


## 2" & 3" Self-Priming Engine Driven Trash Pumps



Model 2S5XHR




Model 3S5XLR

IPT Portable High Volume, Self-priming Centrifugal Trash pumps come standard with a cast iron impeller to resist abrasion and **one tool serviceability** for easy cleanout. Pumps are designed to handle liquids with solids content or dissolved solids and debris. All pumps feature aluminum housing, cast iron wearparts, built-in check valve, suction strainer and heavy duty steel roll frame. Heavy duty cast iron flanges with male NPT threads that rotates in 90° increments. Easy access fill plug on discharge port.

- **Cast Aluminum with Cast Iron Wearparts**
- **Silicon Carbide/Viton® Mechanical Seal**
- **EPDM/EPR O-Rings Standard with Optional Viton®**
- **2" or 3" Removable Male NPT Suction and Discharge Ports**
- **Discharge Rotates in 90° Increments**
- **Engine Options: Honda, LCT Storm Force Gasoline or Hatz Diesel Engines**
- **Easy Clean Out with One Tool Serviceability**
- **Maximum Solids Handling up to 1-1/4"**
- **Solids Handling and Dirty Water Design**
- **Maximum Flow up to 290 GPM**
- **Maximum Head up to 125 Ft.**
- **Self-Priming to 26 Ft.**
- **Wheel Kit Optional**

Performance of Engine Driven Self-Priming Trash Pumps



(\* ) Convert to psi, divide by 2.31 Liquid - Water specific gravity 1.0

# Engine Driven Self-Priming Trash Pumps

## 2" Trash Pumps

Model	HP Class♦	Curve	Port	Driver	Seal	Run Time (Hours)	Tank Size (Gal/Ltr.)	Ship Wt. (Lbs.)
<b>2S5XLR</b>	5 HP	A	2" NPT	LCT 208CC▲	Viton® / SIC-SIC	2.2	0.71/2.7	90
<b>2S5XHR</b>	5 HP	A	2" NPT	Honda GX160▲	Viton® / SIC-SIC	2.0	0.82/3.1	90
<b>2S7XZR</b>	5 HP	A	2" NPT	Hatz Diesel 1B30++	Viton® / SIC-SIC	2.7	1.32/5.0	130


**Construction: Cast Aluminum with Cast Iron Components**

♦ HP Class represents market category and is not intended to define actual horsepower.

++ 12V DC Electric Start (Battery Not Included—use BCI Group: U1 or U2)

▲ Oil Alert Included

**Maximum Solids Handling Capacity: 1" Diameter**



## 3" Trash Pumps

Model	HP Class♦	Curve	Port	Driver	Seal	Run Time (Hours)	Tank Size (Gal/Ltr.)	Ship Wt. (Lbs.)
<b>3S5XLR</b>	5 HP	B	3" NPT	LCT 208CC▲	Viton® / SIC-SIC	2.2	0.71/2.7	100
<b>3S5XHR</b>	5 HP	B	3" NPT	Honda GX200▲	Viton® / SIC-SIC	2.5	0.82/3.1	100
<b>3S7XZR</b>	5 HP	B	3" NPT	Hatz Diesel 1B30++	Viton® / SIC-SIC	2.7	0.79/3.0	135

**Construction: Cast Aluminum with Cast Iron Components**

♦ HP Class represents market category and is not intended to define actual horsepower.

++ 12V DC Electric Start (Battery Not Included—use BCI Group: U1 or U2)

▲ Oil Alert Included

**Maximum Solids Handling Capacity: 1 1/4" Diameter**

Model	L**	W	H	A
<b>2S5X/3S5X*</b>	24.0 [60.9]	19.5 [49.5]	19.9 [50.5]	7.4 [18.7]
<b>2S7X/3S7X*</b>	31.0 [78.7]	22.5 [57.1]	23.6 [59.9]	7.9 [20.0]

(\*) Standard NPT (Male) Pipe Thread.

(\*\*) This dimension may vary due to engine manufacturer's specifications.

NOTE: Dimensions are in inches (centimeters) and have a tolerance of ± 1/8".

### 5/8" Threaded Pump Kit - Cast Aluminum

Model*	Seal Type & Elastomer/Faces	Mounting	Ship Wt. (Lbs.)
<b>2S5X</b>	Viton® / SIC-SIC	Handle	40
<b>3S5X</b>	Viton® / SIC-SIC	Handle	45

\*Does not include roll cage or engine, unassembled

## Standard Features

- Cast Iron Impeller
- One Tool Serviceability Tool Included with Engine Driven Models
- Silicon Carbide Mechanical Seal with Graphite Impregnated Seat and Viton® Elastomers
- Heavy Duty Steel Roll Frame and Strainer Included
- Built-in EPDM/EPR Check Valve
- Removable/Replaceable Cast Iron Suction/Discharge Ports
- Discharge Port Rotates in 90° Increments
- Choice of Honda, LCT Storm Force Gasoline or Hatz Diesel Engine
- Vibration Dampening Feet
- Maximum Temperature 180° F
- Optional Viton® O-ring / Check Valve Available
- Pedestal Version Available
- Optional Wheel Kit Available
- QSP - Quick Ship Pumps for Many Models