

SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200, WHMIS 2015 and Safe Work Australia

Revision date: 29 April 2024 **Date of previous issue:** 26 April 2018 **SDS No.** 463AGY-2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

ARC 855N (Part A) (GY)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

Uses advised against: No information available

Reason why uses advised against: Not applicable

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
 860 Salem Street
 Groveland, MA 01834-1507, USA
 Tel. +1 978-469-6446
 (Mon. - Fri. 8:30 - 5:00 PM EST)
 SDS requests: www.chesterton.com
 E-mail (SDS questions): ProductSDSs@chesterton.com
 E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,
 Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055

1.4. Emergency telephone number

24 hours per day, 7 days per week
 Call Infotrac: 1-800-535-5053
 Outside N. America: +1 352-323-3500 (collect)
 NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to 29 CFR 1910.1200 / WHMIS 2015 / Safe Work Australia / GHS

Skin irritation, Category 2, H315
 Skin sensitization, Category 1, H317
 Eye irritation, Category 2, H319
 Hazardous to the aquatic environment, Chronic, Category 2, H411

2.1.2. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements

Labeling according to 29 CFR 1910.1200 / WHMIS 2015 / Safe Work Australia / GHS

Hazard pictograms:



Signal word:

Warning

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:	P261	Avoid breathing vapours.
	P264	Wash hands thoroughly after handling.
	P272	Contaminated work clothing must not be allowed out of the workplace.
	P273	Avoid release to the environment.
	P280	Wear protective gloves and eye/face protection.
	P302/352	IF ON SKIN: Wash with plenty of soap and water.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337/313	If eye irritation persists: Get medical advice/attention.
	P362/364	Take off contaminated clothing and wash it before reuse.
	P391	Collect spillage.
	P501	Dispose of contents/container to an approved waste disposal plant.

Supplemental information: Contains epoxy constituents. See information supplied by the manufacturer.

2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Hazardous Ingredients ¹	% Wt.	CAS No.	GHS Classification
Epoxy resin (number average molecular weight <= 700)	25-35	9003-36-5* and 1675-54-3**	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 ^a Aquatic Chronic 2, H411
Other ingredients:			
Silicon carbide	25-35	409-21-2	Not classified***
Graphite	1-5	7782-42-5	Not classified***
Titanium dioxide	1-5	13463-67-7	Not classified*** ^b
Silica (Quartz)	< 0.2	14808-60-7	Not classified***

* Alternative CAS No: 28064-14-4. **Alternative CAS No: 25068-38-6. ***Substance with a workplace exposure limit.

^a Applies to CAS no. 1675-54-3 only.

^b Contains less than 1 % of particles with aerodynamic diameter ≤ 10 µm.

For full text of H-statements: see SECTIONS 2.2 and 16.

¹ Classified according to: 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), WHMIS 2015, Safe Work Australia, GHS

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Not applicable

Skin contact: Remove contaminated clothing. Wash skin with soap and water. Consult physician if irritation develops.

Eye contact: Flush eyes for at least 15 minutes with large amounts of water. Consult physician if irritation develops.

Ingestion: Do not induce vomiting. Contact physician immediately.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. See section 8.2.2 for recommendations on personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Moderate eye and skin irritant. May cause skin sensitization as evidenced by rashes or hives.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon dioxide, dry chemical, foam or water fog

Unsuitable extinguishing media: None known

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products: phenolics, carbon monoxide, carbon dioxide, halogenated compounds, aldehydes

Other hazards: None

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Australian HAZCHEM Emergency Action Code: 2 Z

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated leather including shoes cannot be decontaminated and should be discarded. Utilize exposure controls and personal protection as specified in Section 8. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		AUSTRALIA ES ³	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Epoxy resin (number average molecular weight <= 700)	N/A	N/A	N/A	N/A	N/A	N/A
Silicon carbide	(total)	15	(total)	10	N/A	10
	(resp.)	5	(resp.)	3		
Graphite	15 mppcf	(resp.)	(resp.)	2	(resp.)	3
Titanium dioxide	N/A	15	N/A	10	N/A	10
Silica (Quartz)	(total)	0.3	(resp.)	0.025	(resp.)	0.05
	(resp.)	0.05				

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

No biological exposure limits noted for the ingredient(s).

8.2. Exposure controls**8.2.1. Engineering measures**

No special requirements. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed.
Protective gloves: Chemical resistant gloves (e.g., butyl rubber, nitrile)
Eye and face protection: Safety goggles.
Other: Impervious clothing as necessary to prevent skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	viscous paste	pH	not applicable
Colour	gray	Kinematic viscosity	870k cps @ 25°C
Odour	sweet	Solubility in water	insoluble
Odour threshold	not determined	Partition coefficient n-octanol/water (log value)	not applicable
Boiling point or range	not applicable	Vapour pressure @ 20°C	not determined
Melting point/freezing point	not applicable	Density and/or relative density	1.9 kg/l
% Volatile (by volume)	< 0.52%	Weight per volume	15.9 lbs/gal.
Flammability	not determined	Vapour density (air=1)	> 1
Lower/upper flammability or explosion limits	not determined	Rate of evaporation (ether=1)	< 1
Flash point	> 116°C (> 240°F)	% Aromatics by weight	0%
Method	Closed Cup	Particle characteristics	not applicable
Autoignition temperature	not applicable	Explosive properties	not applicable
Decomposition temperature	not determined	Oxidising properties	not applicable

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Extreme heat above 149°C (300°F).

10.5. Incompatible materials

Strong mineral acids and bases, strong organic bases and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Skin and eye contact. Personnel with pre-existing skin or lung allergies may be aggravated by exposure.
Acute toxicity -

Oral: Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin	LD50, rat	> 5000 mg/kg
Graphite	LD50, rat	> 2000 mg/kg
Silicon carbide	NOAEL, rat	2000 mg/kg
Titanium dioxide	LD50, rat	> 10000 mg/kg

Dermal: Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin	LD50, rabbit	> 2000 mg/kg
Silicon carbide	NOAEL, rat	2000 mg/kg
Titanium dioxide	LD50, rabbit	> 10000 mg/kg

Inhalation:

Substance	Test	Result
Epoxy resin	LC0, rat, 5-8 h	No mortality at vapor saturation level
Graphite	LC50, rat, 4 h	> 2 mg/l
Titanium dioxide	LC50, rat, 4 h	> 6.82 mg/l

Skin corrosion/irritation: Irritating to skin.

Substance	Test	Result
Epoxy resin	Skin irritation, rabbit	Moderate irritation
Graphite	Skin irritation, rabbit	Not irritating
Titanium dioxide	Skin irritation, rabbit	Not irritating

Serious eye damage/irritation: Irritating to eyes.

Substance	Test	Result
Epoxy resin	Eye irritation, rabbit	Moderate irritation
Titanium dioxide	Eye irritation, rabbit	Not irritating

Respiratory or skin sensitisation:

May cause skin sensitization as evidenced by rashes or hives.

Substance	Test	Result
Epoxy resin	Skin sensitization, guinea pig	Sensitizing
Graphite	Skin sensitization, mouse	Not sensitizing
Titanium dioxide	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity: Epoxy resin, Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

Carcinogenicity: The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have classified inhaled silica as a human carcinogen. IARC has designated inhaled titanium dioxide as possibly carcinogenic to humans (group 2B). The silica and titanium dioxide in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin: based on available data, the classification criteria are not met.

Reproductive toxicity: Epoxy resin, Graphite, Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

STOT – single exposure: Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

STOT – repeated exposure: Repeated inhalation of respirable free silica may cause scarring of the lungs with cough and shortness of breath. Silicosis, a delayed lung injury that is a disabling, progressive and sometimes fatal pulmonary fibrosis, may result. Prolonged, excessive inhalation of Graphite dust has caused emphysema and pneumoconiosis. The silica and graphite in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin, Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

Substance	Test	Result
Epoxy resin (CAS no. 1675-54-3)	Sub-chronic NOAEL, oral, 90 days, rat, male / female (OECD 408)	50 mg/kg bw/day
Epoxy resin (CAS no. 1675-54-3)	Sub-chronic NOAEL, dermal, 90 days, rat, male / female (OECD 411)	10 mg/kg bw/day
Epoxy resin (CAS no. 1675-54-3)	Sub-chronic NOAEL, dermal, 90 days, mouse, male (OECD 411)	100 mg/kg bw/day
Epoxy resin (CAS no. 9003-36-5)	Sub-chronic NOAEL, oral, 90 days, rat, male / female (OECD 408)	250 mg/kg bw/day

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Epoxy resin (number average molecular weight \leq 700) is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment (LC50/EC50 between 1 and 10 mg/l in the most sensitive species). Epoxy resin: chronic NOEC, 21 days, Daphnia magna (OECD 211) = 0.3 mg/l.

12.2. Persistence and degradability

Unreacted components (Parts A and B), improperly released to the environment, can cause ground and water pollution. Epoxy resin: not readily biodegradable (biodegradation, OECD 301F, 28 days: 5%).

12.3. Bioaccumulative potential

Epoxy resin: Octanol/water partition coefficient (log Kow) = 2.64 – 3.78, low to moderate potential for bioaccumulation.

12.4. Mobility in soil

viscous paste. Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Epoxy resin: if product enters soil, it will be mobile and may contaminate groundwater (log Koc \leq 3.65).

12.5. Endocrine disrupting properties

None known

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Combine resin and curative. The final cured material is considered nonhazardous. Unreacted components are a special waste. Landfill sealed containers with stabilized and solidified liquids with a properly licensed facility. May be incinerated at an appropriate facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number or ID number

ADG/ADR/RID/ADN/IMDG/ICAO: UN3082

TDG: UN3082

US DOT: UN3082

14.2. UN proper shipping name

ADG/ADR/RID/ADN/IMDG/ICAO: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

TDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

US DOT: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/ICAO: 9
 TDG: 9
 US DOT: 9

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/ICAO: III
 TDG: III
 US DOT: III

14.5. Environmental hazards

MARINE POLLUTANT

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Maritime transport in bulk according to IMO instruments

NOT APPLICABLE

14.8. Other information

US DOT: ERG NO.171,

MAY BE SHIPPED AS NON-RESTRICTED IN NON-BULK PACKAGINGS (119 GALLONS OR LESS) BY MOTOR VEHICLE, RAIL CAR OR AIRCRAFT.

(49 CFR 171.4(C))

IMDG: EMS. F-A, S-F

MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS. (IMDG CODE AMENDMENT 37-14, 2.10.2.7)

ICAO/IATA: MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS. (IATA DANGEROUS GOODS REGULATION 56TH EDITION, 4.4 SPECIAL PROVISIONS A197)

ADR: CLASSIFICATION CODE M6 TUNNEL RESTRICTION CODE (E)

MAY BE SHIPPED AS NON-RESTRICTED IN SINGLE OR COMBINATION PACKAGINGS CONTAINING A NET QUANTITY PER SINGLE OR INNER PACKAGING OF 5 L OR LESS. (ADR 2015 VOLUME 1, CHAPTER 3.3 SPECIAL PROVISIONS 375)

ADG HAZCHEM CODE: ●3Z HIN: 90

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. National regulations****US EPA SARA TITLE III****312 Hazards:**

Chemicals subject to reporting requirements of Section 313 of EPCRA and of 40 CFR 372:

Skin irritation
 Skin sensitization
 Eye irritation

None

TSCA: All chemical components are listed or exempted.

Other national regulations: None

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADG: Australian Dangerous Goods Code
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE: Acute Toxicity Estimate
 BCF: Bioconcentration Factor
 cATpE: Converted Acute Toxicity point Estimate
 ES: Exposure Standard
 GHS: Globally Harmonized System
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 LC50: Lethal Concentration to 50 % of a test population
 LD50: Lethal Dose to 50% of a test population
 LOEL: Lowest Observed Effect Level
 N/A: Not Applicable
 NA: Not Available
 NOEC: No Observed Effect Concentration
 NOEL: No Observed Effect Level
 OECD: Organization for Economic Co-operation and Development
 (Q)SAR: Quantitative Structure-Activity Relationship
 REL: Recommended Exposure Limit
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure
 STOT SE: Specific Target Organ Toxicity, Single Exposure
 TDG: Transportation of Dangerous Goods (Canada)
 TWA: Time Weighted Average
 US DOT: United States Department of Transportation
 WHMIS: Workplace Hazardous Materials Information System
 Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
 Chemical Classification and Information Database (CCID)
 European Chemicals Agency (ECHA) - Information on Chemicals
 Hazardous Chemical Information System (HCIS)
 National Institute of Technology and Evaluation (NITE)
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to GHS:

Classification	Classification procedure
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1, H317	Calculation method
Eye Irrit. 2, H319	Calculation method
Aquatic Chronic 2, H411	Calculation method

Relevant H-statements: H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H411: Toxic to aquatic life with long lasting effects.

Hazard pictogram names: Exclamation mark, environment

Further information: None

Date of last revision: 29 April 2024

Changes to the SDS in this revision: Sections 1.2, 1.3, 1.4, 2.1, 2.2, 3, 4.1, 5.2, 5.3, 8.1, 9.1, 10.6, 11, 12.1, 12.3, 12.5, 13, 14.8, 15.1, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.