

Model: PFEV512

Features:

General purpose pump for residential, light industrial and commercial sump or effluent applications.

- **DISCHARGE:** 2" NPT, Female, Vertical
- **LIQUID TEMPERATURE:** 77°F Continuous
- **MOTOR HOUSING/ VOLUTE:** Cast Iron, Class 30
- **SEAL PLATE:** Cast Iron, Class 30
- **IMPELLER:** Multi-Vane vortex, Cast Iron, Class 30
- **SHAFT & HARDWARE:** Stainless steel
- **PAINT:** Industrial grade powder coating
- **O-RINGS:** Buna-N
- **SEAL:** Inboard, Single mechanical, .50", Type "C", U.S. Seal, Oil Filled Chamber, Carbon/Ceramic/Buna-N with Secondary Exclusion Seal
- **UPPER BEARING:** Sleeve, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 20FT., SJTW, 16/3 Cord with plug, Pressure Grommet for Sealing and Strain Relief.
- **MOTOR:** Class B Insulation, Oil Filled
- **SINGLE PHASE:** Permanent Split Capacitor (PSC), Includes overload protection in motor
- **WARRANTY:** 2 year

 **WARNING: CANCER AND REPRODUCTIVE HARM-**
WWW.P65WARNINGS.CA.GOV



**Submersible Effluent
2" Discharge,
3/4" Spherical Solids
Manual Operation**



MODEL	HP	Hz	Volts/ Ph	RPM	Full Load Amps	NEMA Start Code	Cord Size	Cord Type	Cord Length	Simplex Control	Duplex Control
PFEV512	0.5	60	115/1	3450	11	H	16/3	SJTW	20Ft	PF1000	PF2000
PFEV512X-30	0.5	60	115/1	3450	11	H	16/3	SJTW	30Ft	PF1000	PF2000
PFEV512X-50	0.5	60	115/1	3450	11	H	16/3	SJTW	50Ft	PF1000	PF2000

IMPORTANT: Remove Plug for use with Control Panel.



Power-Flo Pumps & Systems

a Power-Flo Technologies company

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

Effluent Pumps - PFEV - 1/2HP - 3450RPM - 60Hz

Sect.
E
Page
7
Rev.
02/2021

Model: PFEV512

Effluent Pumps - PFEV - 1/2HP - 3450RPM - 60Hz

