

Model: PFV512A

Features:

Submersible sewage pump designed for typical raw sewage and typical septic tank/effluent applications..

- **DISCHARGE:** 2" NPT, Female, Vertical
- **LIQUID TEMPERATURE:** 77°F Continuous
- **MOTOR HOUSING/ VOLUTE:** Cast Iron, Class 30
- **IMPELLER:** Multi-vane, vortex , Cast Iron, Class 30
- **SHAFT & HARDWARE:** Stainless steel
- **PAINT:** Industrial grade powder coating
- **O-RINGS:** Buna-N
- **SEAL:** Inboard, Single mechanical, .50 inch, Oil Filled reservoir, Carbon/Ceramic/Buna-N with Secondary Exclusion Seal
- **UPPER BEARING:** Sleeve, oil lubricated
- **LOWER BEARING:** Single row, ball, oil lubricated
- **POWER CORD:** 20Ft., SJTW, 16/3 Cord with plug, Pressure Grommet for Sealing and Strain Relief.
- **MOTOR:** Class B Insulation, Oil Filled, Squirrel Cage Induction
- **SINGLE PHASE:** Permanent Split Capacitor (PSC), Includes overload protection in motor
- **LEVEL CONTROL:** Wide Angle, Mechanical, Normally Open (N/O), 16/2, SJOW, 20Ft cord with Piggy-Back plug, P/N: PF512040
- **WARRANTY:** 2 year

 **WARNING:** CANCER AND REPRODUCTIVE HARM-
WWW.P65WARNINGS.CA.GOV



**Submersible Sewage
2" Discharge,
2" Spherical Solids
Wide Angle Float**



MODEL	HP	VOLTS	PHASE	HZ	RPM	FULL LOAD AMPS	NEMA START CODE	CORD SIZE	CORD TYPE	CORD O.D.	Simplex Control	Duplex Control
PFV512A	0.5	115	1	60	3450	10.5	H	16/3	SJTW	0.335	n/a	n/a



Power-Flo Pumps & Systems

a Power-Flo Technologies company

877-24PUMPS • fax: 516-812-6897 • www.powerflopumps.com

2" - Sewage Pumps - PFV, 1/2HP - 3450RPM - 60Hz

Model: PFV512A

2" - Sewage Pumps - PFV, 1/2HP - 3450RPM - 60Hz

